



PRODUCT FEATURES

- Ultrafast Recovery Time
- Soft Recovery Characteristics
- Low Recovery Loss
- Low Forward Voltage
- High Surge Current Capability
- Low Leakage Current

APPLICATIONS

- Freewheeling, Snubber, Clamp
- Inversion Welder
- Plating Power Supply
- Ultrasonic Cleaner and Welder
- Converter & Chopper, PFC
- UPS



DESCRIPTION

FRED from MacMic utilizes advanced processing techniques to achieve ultrafast recovery times and higher forward current. Its soft recovery characteristics and high reliability suit for wide industrial applications.

ABSOLUTE MAXIMUM RATINGS

$T_C=25^{\circ}\text{C}$ unless otherwise specified

Symbol	Parameter	Test Conditions	Values	Unit
V_R	Maximum D.C. Reverse Voltage		900	V
V_{RRM}	Maximum Repetitive Reverse Voltage		900	V
$I_{F(AV)}$	Average Forward Current	$T_C=25^{\circ}\text{C}$	80	A
$I_{F(RMS)}$	RMS Forward Current		110	A
I_{FSM}	Non-Repetitive Surge Forward Current	$T_J=25^{\circ}\text{C}$, $t=10\text{ms}$, 50Hz, Sine	500	A
P_D	Power Dissipation		125	W
T_J	Junction Temperature		-55 to +150	$^{\circ}\text{C}$
T_{STG}	Storage Temperature Range		-55 to +150	$^{\circ}\text{C}$
Torque	Module-to-Sink	Recommended (M3)	1.1	N·m
$R_{th(J-C)}$	Thermal Resistance	Junction-to-Case, Per Diode	1	$^{\circ}\text{C}/\text{W}$
Weight			6.5	g

ELECTRICAL CHARACTERISTICS

$T_C=25^{\circ}\text{C}$ unless otherwise specified

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
I_{RM}	Reverse Leakage Current	$V_R=900\text{V}$	--	--	10	μA
		$V_R=900\text{V}$, $T_J=125^{\circ}\text{C}$	--	--	10	mA
V_F	Forward Voltage	$I_F=80\text{A}$	--	2.2	3	V
		$I_F=80\text{A}$, $T_J=125^{\circ}\text{C}$	--	1.9	--	V
t_{rr}	Reverse Recovery Time	$I_F=1\text{A}$, $V_R=30\text{V}$, $di_F/dt=-200\text{A}/\mu\text{s}$	--	30	--	ns
t_{rr}	Reverse Recovery Time	$V_R=450\text{V}$, $I_F=80\text{A}$ $di_F/dt=-200\text{A}/\mu\text{s}$, $T_J=25^{\circ}\text{C}$	--	65	--	ns
I_{RRM}	Max. Reverse Recovery Current		--	6.5	--	A
t_{rr}	Reverse Recovery Time	$V_R=450\text{V}$, $I_F=80\text{A}$ $di_F/dt=-200\text{A}/\mu\text{s}$, $T_J=125^{\circ}\text{C}$	--	150	--	ns
I_{RRM}	Max. Reverse Recovery Current		--	12	--	A
S			--	1	--	--




Fig1. Forward Voltage Drop vs Forward Current




Fig2. Reverse Recovery Time vs di_F/dt




Fig3. Reverse Recovery Current vs di_F/dt




Fig4. Reverse Recovery Charge vs di_F/dt




Fig5. Forward current vs. Case temperature




Fig6. Transient Thermal Impedance





Fig7. Diode Reverse Recovery Test Circuit and Waveform



Dimensions in Millimeters

Fig8. Package Outline