

PRODUCT FEATURES

- IGBT³ CHIP(Trench+Field Stop technology)
- High short circuit capability,self limiting short circuit current
- $V_{CE(sat)}$ with positive temperature coefficient
- Fast switching and short tail current
- Free wheeling diodes with fast and soft reverse recovery
- Low switching losses

APPLICATIONS

- High frequency switching application
- Medical applications
- Motion/servo control
- UPS systems



IGBT-inverter

ABSOLUTE MAXIMUM RATINGS ($T_C=25^\circ\text{C}$ unless otherwise specified)

| Symbol | Parameter/Test Conditions | Values | Uni |
|-----------|---|------------------------|-----|
| V_{CES} | Collector Emitter Voltage $T_J=25^\circ\text{C}$ | 650 | V |
| V_{GES} | Gate Emitter Voltage | ± 20 | |
| I_C | DC Collector Current $T_C=25^\circ\text{C}$ | 200 | A |
| | | $T_C=80^\circ\text{C}$ | |
| I_{CM} | Repetitive Peak Collector Current $t_p=1\text{ms}$ | 300 | |
| P_{tot} | Power Dissipation Per IGBT | 428 | W |

Diode-inverter

ABSOLUTE MAXIMUM RATINGS ($T_C=25^\circ\text{C}$ unless otherwise specified)

| Symbol | Parameter/Test Conditions | Values | Uni |
|-------------|---|--------|------------------|
| V_{RRM} | Repetitive Reverse Voltage $T_J=25^\circ\text{C}$ | 650 | V |
| $I_{F(AV)}$ | Average Forward Current $T_C=25^\circ\text{C}$ | 150 | A |
| I_{FRM} | Repetitive Peak Forward Current $t_p=1\text{ms}$ | 300 | |
| I^2t | $T_J=125^\circ\text{C}, t=10\text{ms}, V_R=0\text{V}$ | 1800 | A ² S |

MacMic Science & Technology Co., Ltd.

Add: #18, Hua Shan Zhong Lu, New District, Changzhou City, Jiangsu Province, P. R. of China
 Tel.: +86-519-85163708 Fax: +86-519-85162291 Post Code: 213022 Website: www.macmicst.com

IGBT-inverter

ELECTRICAL CHARACTERISTICS ($T_C=25^\circ\text{C}$ unless otherwise specified)

| Symbol | Parameter/Test Conditions | | Min. | Typ. | Max. | Uni |
|---------------|--|--|-------------------------|------|------|---------------|
| $V_{GE(th)}$ | Gate Emitter Threshold Voltage | $V_{CE}=V_{GE}, I_C=2.4\text{mA}$ | 4.9 | 5.8 | 6.5 | V |
| $V_{CE(sat)}$ | Collector Emitter Saturation Voltage | $I_C=150\text{A}, V_{GE}=15\text{V}, T_J=25^\circ\text{C}$ | | 1.45 | 1.9 | |
| | | $I_C=150\text{A}, V_{GE}=15\text{V}, T_J=150^\circ\text{C}$ | | 1.7 | | |
| I_{CES} | Collector Leakage Current | $V_{CE}=650\text{V}, V_{GE}=0\text{V}, T_J=25^\circ\text{C}$ | | | 1 | mA |
| | | $V_{CE}=650\text{V}, V_{GE}=0\text{V}, T_J=150^\circ\text{C}$ | | | 5 | mA |
| I_{GES} | Gate Leakage Current | $V_{CE}=0\text{V}, V_{GE}=\pm 15\text{V}, T_J=150^\circ\text{C}$ | -400 | | 400 | nA |
| R_{gint} | Integrated Gate Resistor | | | 2 | | Ω |
| Q_g | Gate Charge | $V_{CE}=300\text{V}, I_C=150\text{A}, V_{GE}=\pm$ | | 0.95 | | μC |
| C_{ies} | Input Capacitance | $V_{CE}=25\text{V}, V_{GE}=0\text{V}, f=1\text{MHz}$ | | 9.3 | | nF |
| C_{res} | Reverse Transfer Capacitance | | | | 290 | |
| $t_{d(on)}$ | Turn on Delay Time | $V_{CC}=300\text{V}, I_C=150\text{A}, R_G=2.2\Omega, V_{GE}=\pm 15\text{V},$ Inductive Load | $T_J=25^\circ\text{C}$ | | 200 | ns |
| | | | $T_J=150^\circ\text{C}$ | | 210 | ns |
| t_r | Rise Time | | $T_J=25^\circ\text{C}$ | | 70 | ns |
| | | | $T_J=150^\circ\text{C}$ | | 80 | ns |
| $t_{d(off)}$ | Turn off Delay Time | $V_{CC}=300\text{V}, I_C=150\text{A}, R_G=2.2\Omega, V_{GE}=\pm 15\text{V},$ Inductive Load | $T_J=25^\circ\text{C}$ | | 300 | ns |
| | | | $T_J=150^\circ\text{C}$ | | 330 | ns |
| t_f | Fall Time | | $T_J=25^\circ\text{C}$ | | 50 | ns |
| | | | $T_J=150^\circ\text{C}$ | | 70 | ns |
| E_{on} | Turn on Energy | $V_{CC}=300\text{V}, I_C=150\text{A}, R_G=2.2\Omega, V_{GE}=\pm 15\text{V},$ Inductive Load | $T_J=25^\circ\text{C}$ | | 0.75 | mJ |
| | | | $T_J=150^\circ\text{C}$ | | 1.2 | mJ |
| E_{off} | Turn off Energy | | $T_J=25^\circ\text{C}$ | | 4 | mJ |
| | | | $T_J=150^\circ\text{C}$ | | 5.15 | mJ |
| I_{SC} | Short Circuit Current | $t_{psc}\leq 6\mu\text{s}, V_{GE}=15\text{V}, T_J=125^\circ\text{C}, V_{CC}=360\text{V}$ | | 750 | | A |
| R_{thJC} | Junction to Case Thermal Resistance (Per IGBT) | | | | 0.35 | K/W |

Diode-inverter

ELECTRICAL CHARACTERISTICS ($T_C=25^\circ\text{C}$ unless otherwise specified)

| Symbol | Parameter/Test Conditions | | Min. | Typ. | Max. | Uni |
|-------------|---|--|------|------|------|---------------|
| V_F | Forward Voltage | $I_F=150\text{A}, V_{GE}=0\text{V}, T_J=25^\circ\text{C}$ | | 1.55 | 1.95 | V |
| | | $I_F=150\text{A}, V_{GE}=0\text{V}, T_J=150^\circ\text{C}$ | | 1.45 | | |
| t_{rr} | Reverse Recovery Time | $I_F=150\text{A}, V_R=300\text{V}$ | | 210 | | ns |
| I_{RRM} | Max. Reverse Recovery Current | $di_F/dt=-1600\text{A}/\mu\text{s}$ | | 95 | | A |
| Q_{RR} | Reverse Recovery Charge | $T_J=150^\circ\text{C}$ | | 11 | | μC |
| E_{rec} | Reverse Recovery Energy | | | 3.5 | | mJ |
| R_{thJCD} | Junction to Case Thermal Resistance (Per Diode) | | | | 0.6 | K/W |

NTC CHARACTERISTICS ($T_C=25^\circ\text{C}$ unless otherwise specified)

| Symbol | Parameter/Test Conditions | | Min. | Typ. | Max. | Uni |
|-------------|---|------------------------|------|------|------|------------|
| R_{25} | Resistance | $T_C=25^\circ\text{C}$ | | 5 | | K Ω |
| $B_{25/50}$ | $R_2 = R_{25} \exp [B_{25/50}(1/T_2 - 1/(298,15 \text{ K}))]$ | | | 3375 | | K |

MODULE CHARACTERISTICS ($T_C=25^\circ\text{C}$ unless otherwise specified)

| Symbol | Parameter/Test Conditions | | Values | Uni |
|------------|-----------------------------|----------------------------|---------|-----|
| T_{Jmax} | Max. Junction Temperature | | 175 | °C |
| T_{Jop} | Operating Temperature | | -40~150 | |
| T_{stg} | Storage Temperature | | -40~125 | |
| V_{isol} | Isolation Breakdown Voltage | AC, 50Hz(R.M.S), t=1minute | 3000 | V |
| CTI | Comparative Tracking Index | | > 200 | |
| Torque | to heatsink | Recommended (M6) | 3~5 | Nm |
| | to terminal | Recommended (M6) | 3~5 | Nm |
| Weight | | | 300 | g |




Figure 1. Typical Output Characteristics IGBT-inverter




Figure 2. Typical Output Characteristics IGBT-inverter




Figure 3. Typical Transfer characteristics IGBT-inverter




Figure 4. Switching Energy vs Gate Resistor IGBT-inverter




Figure 5. Switching Energy vs Collector Current IGBT-inverter




Figure 6. Reverse Biased Safe Operating Area




Figure 7. Collector Current vs Case temperature IGBT -inverter




Figure 8. Forward current vs Case temperature




Figure 9. Diode Forward Characteristics Diode -inverter




Figure 10. Switching Energy vs Gate Resistor Diode -inverter




Figure 11. Switching Energy vs Forward Current Diode-inverter




Figure 12. Transient Thermal Impedance of Diode and IGBT-inverter




Figure 13. NTC Characteristics





Figure 14. Circuit Diagram



Dimensions in (mm)
 Figure 15. Package Outline